



About HIC Rubber V-Belts


ISO 9001 certified HIC International, 1988 formed company, Delhi based Indian producer of **High-Speed Fan Motor Drive**, **Super Power-Rated Mechanical Power Transmission Antistatic Rubber V Belts**, exporting to industries in Asia, Europe, Africa, Oceania, America to customer's thorough satisfaction.

Full-proof **Quality Assurance Plan** details on: www.UniversalDelhi.org


Credentials of Quality World-wide Supplies details on: www.Rubber-Steel-Industrial-Products.com

Range of Tailor-made **Motor Power-transmission Products** Manufacturing details on: www.hicRubber.com


SUPER-POWER RATED




Even Load Banded
as per DIN 7753




Extreme Speed V Ribbed
Automotive PJ, PK, PL, PM
per ISO 9982




High Life Wedge SPA,
SPB, SPC, SPZ per BS 3790



Double Sided Power
BB, CC per DIN 7722



Classic A, B, C, D, E
per IS 2494



Efficient Synchronous Timing
XL, L, H, XH, HTD per DIN 7721

Vendor Data for Supplier Enlistment information on: www.hicPowerDrive.com

Follow us:



 **Why Choose HIC UNIVERSAL
Cogged V Belt?**

Superb Heat and Fatigue Resistant Classic, Wedge Sections A,B,C,D,E | SPC,SPB,XPA,SPZ | 5V |BB | Ax, Bx | 6PK,8PK
Enables High Power Drive of industrial Fans, Train Lighting Alternators

Higher Horsepower Rated Shock Loads Tolerant Narrow Banded
Prevents Whip & Eases Replacement in Agricultural Combine Harvester, Stone Crusher, Compressors

Zero Slippage Polyester or Aramid Cord Ribbed Poly-V Sizes
Allows Silent Compact Higher Speed Drive in Automotive, Machine Tools



Antistatic Cogged, Wrapped Featuring Minimal Elongation
Aids High Power Transmission in industrial Motors, Pumps, Turbine



MANUFACTURING RANGE:

Wedge, Classic, Narrow Wrapped and Cogged, SPC/SPB/XPA/SPZ, E/D/C/Bx/A/FHP, 3V/5V, BB/CC, up to 675 inch L, as per IS 2494
Banded and Double Hexagonal, RA/RB/RC, R5V/R8V, BB/CC, 2~8 Bands, up to 8890 mm L, as per ISO 5290
Multi Ribbed Poly V, 3PK/4PK/5PK/6PK/8PK, up to 2500 mm L, as per DIN 7753

Technical Specifications download from: www.hic-india.com

RFQ rubber v-belt specs. As stated below, in English language please, to quote price offer:

- 1. Section or Top Width x Thickness and Size of v belt, Li/ La/ Lp
- 2. Quantity- Numbers

